

STRAIT-FLEX®

New Concept Drywall Products

ARCH-FLEX II

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC tight fibered cotton composite corner tape that is 3.33” wide nominal, .026” thick, with rigid .042” tempered wire hot glue melted into the fold. Arch-Flex II is available in 8’, 9’, 10’; lengths and custom lengths are also available. Strait-Flex Arch-Flex II is very stable with temperature changes and very rigid while maintaining its flexibility and ease of repair from damage.
ADVANTAGES	<ul style="list-style-type: none"> No callbacks on outside 90-degree corners due to cracking or denting Arch Flex II creates a fast, perfect, outside corner that can be installed by an apprentice Damage resistant design Withstands settling, lumber shrinkage and temperature variation Faster hanging and finishing time (guarantee) Will not shrink, blister, tear or wrinkle Installation does not require fasteners, stapling, or any special tools Can run through hopper to mud both sides Material can be second coated immediately Material will not fuzz-up during sanding Water resistant, rustproof Saves 25-50% on installation time
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	<ul style="list-style-type: none"> Apply using liberal coat of all-purpose compound to corner or angle with joint knife. Arch-Flex II can also be put through a hopper to mud both sides. Press Arch-Flex II into wet compound, adjust if necessary to create straight arch and remove excess compound. Apply second coat of compound “immediately”, lightly skim coat surface of Arch-Flex II. Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface. Painted surface of Arch-Flex II must be thoroughly dry before applying second paint coat.
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: