

# STRAIT-FLEX®

*New Concept Drywall Products*

## ARCH-STICK

<b>DESCRIPTION (Speed, Perfection and Longevity)</b>	Patented PVC tight fibered cotton composite corner tape that is 3.33” wide nominal, .026” thick, with rigid .042” tempered wire hot glue melted into the fold. Arch-Stick is available in 8’, 9’, 10’; lengths and custom lengths are also available. Strait-Flex Arch-Stick is very stable with temperature changes and very rigid while maintaining its flexibility and ease of repair from damage.
<b>ADVANTAGES</b>	<ul style="list-style-type: none"> <li>No callbacks on outside 90-degree corners due to cracking or denting</li> <li>Backbone Big Stick creates a fast, perfect, outside corner that can be installed by an apprentice</li> <li>Damage resistant design</li> <li>Withstands settling, lumber shrinkage and temperature variation</li> <li>Faster hanging and finishing time (guarantee)</li> <li>Will not shrink, blister, tear or wrinkle</li> <li>Installation does not require fasteners, stapling, or any special tools</li> <li>Can run through hopper to mud both sides</li> <li>Material can be second coated immediately</li> <li>Material will not fuzz-up during sanding</li> <li>Water resistant, rustproof</li> <li>Saves 25-50% on installation time</li> </ul>
<b>WARRANTY</b>	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
<b>DIRECTIONS</b>	<ul style="list-style-type: none"> <li>Apply using liberal coat of all-purpose compound to corner or angle with joint knife. Arch-Stick can also be put through a hopper to mud both sides.</li> <li>Press Arch-Stick into wet compound, adjust if necessary to create straight arch and remove excess compound.</li> <li>Apply second coat of compound “immediately”, lightly skim coat surface of Arch-Stick.</li> <li>Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface.</li> <li>Painted surface of Arch-Stick must be thoroughly dry before applying second paint coat.</li> </ul>
<b>STORAGE</b>	Store in dry place protected from moisture

**Submittal Approvals:**

Job Name:	
Contractor:	Date: