

ARCH-FLEX

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC tight fibered cotton composite corner tape that is 3.33” wide nominal, .026” thick and is available in 8’, 9’, 10’; lengths and custom lengths are also available. Strait-Flex Arch Stick is very stable with temperature changes and is flexible while maintaining it’s rigidity when wet.
ADVANTAGES	<ul style="list-style-type: none"> • Saves an average of 50% on installation time over other products • Long, continuous arches and curves installed in one piece • Material can be second coated immediately • Only requires light skim coat to finish • Resists denting, paint chipping and edge cracking • Material will not blister or fuzz up when sanded • Continuous roll allows long, continuous arches and curves to be installed in one piece • Easy installation using standard compound -- No special tools, fasteners or stapling are required • Water resistant and rustproof. • No nail pops or paint chipping.
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	<ul style="list-style-type: none"> • Measure entire arch application by using Arch-Flex as a tape measure, cut 1” longer than required. Fold Arch-Flex completely in half, and then fold tear strip edge back against product and remove. • If using Arch-Flex in a transition from a straight corner to an arch corner, mark transition points before folding. • Then fold Arch-Flex completely in half, cut tear strip at transition points, fold tear strip back against product and remove. • Apply all purpose compound to edge and install Arch-Flex from one end pressing firmly into compound. • Arch corner roller can greatly improve speed and ease of installation. • Wipe down compound and adjust to smooth curve. Second coat may be applied immediately or wait until dry for a second coat. • Do not use lightweight compounds for bed coat.
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: