



BACKBONE BIG-STICK OUTSIDE

<p>DESCRIPTION (Speed, Perfection and Longevity)</p>	<p>Patented PVC tight fibered cotton composite corner tape that is 3.33” wide nominal, .026” thick, with rigid .042” tempered wire hot glue melted into the fold. Backbone Big-Stick is available in 8’, 9’, 10’; lengths and custom lengths are also available. Strait-Flex Backbone Big-Stick Outside is very stable with temperature changes and very rigid while maintaining its flexibility and ease of repair from damage.</p>
<p>ADVANTAGES</p>	<ul style="list-style-type: none"> • No callbacks on outside 90-degree corners due to cracking or denting • Backbone Big Stick creates a fast, perfect, outside corner that can be installed by an apprentice • Damage resistant design • Withstands settling, lumber shrinkage and temperature variation • Faster hanging and finishing time (guarantee) • Will not shrink, blister, tear or wrinkle • Installation does not require fasteners, stapling, or any special tools • Can run through hopper to mud both sides • Material can be second coated immediately • Material will not fuzz-up during sanding • Water resistant, rustproof • Saves 25-50% on installation time
<p>WARRANTY</p>	<p>Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.</p>
<p>DIRECTIONS</p>	<ul style="list-style-type: none"> • Apply using liberal coat of all-purpose compound to corner or angle with joint knife. Backbone Big Stick can also be put through a hopper to mud both sides. • Press Backbone Big Stick into wet compound, adjust if necessary to create straight line and remove excess compound. • Apply second coat of compound “immediately”, lightly skim coat surface of Backbone Big Stick. • Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface. • Painted surface of Backbone Big Stick must be thoroughly dry before applying second paint coat.
<p>STORAGE</p>	<p>Store in dry place protected from moisture</p>

Submittal Approvals:

Job Name:

Contractor:	Date:
-------------	-------