

STRAIT-FLEX®

New Concept Drywall Products

BIG-STICK INSIDE 90°

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC tight fibered cotton composite corner tape that is 2.75" wide, .026" thick and comes in 8', 9', 10' and custom lengths. Strait-Flex Big-Stick Inside is very stable with temperature changes and is flexible while maintaining it's rigidity when wet.
ADVANTAGES	<ul style="list-style-type: none"> • No callbacks on all inside 90-degree corners due to cracking or denting • Big-Stick Inside creates a fast, perfect, inside corner that can be installed by an apprentice • Damage proof design • Withstands settling, lumber shrinkage and temperature variation • Faster hanging and finishing time guarantee • Will not shrink, blister, tear or wrinkle • Installation does not require fasteners, stapling, or any special tools • Can run through hopper to mud both sides • Material can be second coated immediately • Material will not fuzz-up during sanding • Water resistant, rustproof • Saves 25-50% on installation time
LIMITATIONS	Not recommended for
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Inside offset corners applied horizontally cannot be guaranteed against cracking. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	<ul style="list-style-type: none"> • Apply using liberal coat of all-purpose compound to corner or angle with joint knife. Big-Stick Inside can also be put through a hopper to mud both sides. • Press Big-Stick Inside into wet compound, adjust if necessary to create straight line and remove excess compound. • Apply second coat of compound "immediately", lightly skim coat surface of Big-Stick Inside. • Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface. • Big-Stick Inside will not fuzz up during sanding. Painted surface of Big-Stick Inside must be thoroughly dry before applying second coat.
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: