

# STRAIT-FLEX®

*New Concept Drywall Products*

## BIG-STICK OUTSIDE

<b>DESCRIPTION (Speed, Perfection and Longevity)</b>	Patented PVC tight fibered cotton composite corner tape that is 3.33" wide nominal, .026" thick using a PUR hot melt down the center fold. Big-Stick Outside is available in 8', 9', 10'; lengths and custom lengths are also available. Strait-Flex Big-Stick Outside is very stable with temperature changes and is flexible while maintaining it's rigidity when wet.
<b>ADVANTAGES</b>	<ul style="list-style-type: none"> <li>• No callbacks on outside 90-degree corners due to cracking or denting</li> <li>• Big Stick creates a fast, perfect, outside corner that can be installed by an apprentice</li> <li>• Damage proof design</li> <li>• Withstands settling, lumber shrinkage and temperature variation</li> <li>• Faster hanging and finishing time (guarantee)</li> <li>• Will not shrink, blister, tear or wrinkle</li> <li>• Installation does not require fasteners, stapling, or any special tools</li> <li>• Can run through hopper to mud both sides</li> <li>• Material can be second coated immediately</li> <li>• Material will not fuzz-up during sanding</li> <li>• Water resistant, rustproof</li> <li>• Saves 25-50% on installation time</li> </ul>
<b>WARRANTY</b>	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
<b>DIRECTIONS</b>	<ul style="list-style-type: none"> <li>• Apply using liberal coat of all-purpose compound to corner or angle with joint knife. Big Stick can also be put through a hopper to mud both sides.</li> <li>• Press Big Stick into wet compound, adjust if necessary to create straight line and remove excess compound.</li> <li>• Apply second coat of compound "immediately", lightly skim coat surface of Big Stick.</li> <li>• Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface.</li> <li>• Big Stick will not fuzz up during sanding. Painted surface of Big Stick must be thoroughly dry before applying second paint coat.</li> </ul>
<b>STORAGE</b>	Store in dry place protected from moisture

**Submittal Approvals:**

Job Name:	
Contractor:	Date: