



MEDIUM and MEDIUM WITH HOLES

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC tight fibered cotton composite corner tape that is 2 1/4" wide, .013" thick and comes in 100' rolls. Strait-Flex Medium and Medium with Holes have recess running the length of tape, which makes folding quick and is adjustable to any angle. Material is very stable with temperature changes and is flexible while maintaining it's rigidity when wet.
ADVANTAGES	<ul style="list-style-type: none"> • Strait-Flex creates a fast, perfect intricate off angles and inside 90° corners. Straightens small framing irregularities. • Forms easily to all angles and corners • Will not shrink, blister, tear, sag or wrinkle. • Water resistant and rustproof. • Saves 25-50% on installation time. • Material can be second coated immediately. • Solid rolls ensure no waste or damage in transit or in rough site conditions. • Does not require fasteners, stapling, or any special tools. • Resists common cracking problems as encountered when using paper tapes. • Requires very light fill coat to finish product. Medium with holes promotes quicker drying time and easy detection of voids or air pockets behind tape.
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	<ul style="list-style-type: none"> • Cut Strait-Flex to desired length. Fold in half at center crease, and adjust to desired angle. • Apply using a liberal coat of all-purpose compound with joint knife. Use tile setting compounds in wet areas. • Press Strait-Flex into wet compound. Adjust if necessary to create straight line and wipe down with joint knife. Immediately apply light skim coat and let dry. • Apply final coat, let dry and sand.
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: