



PIPE PATCH .50" and .75"

<p>DESCRIPTION (Speed, Perfection and Longevity)</p>	<p>Patented PVC fiber composite material patch that is 2-7/8" in diameter, .011" thick and comes in 100 pieces per box, 5 boxes per case. Pipe Patch is a drywall patch used for 1/2" and 3/4" copper plumbing pipe and 1 1/4" PVC drain pipe. It is pre-cut to fit 1/2" and 3/4" copper plumbing pipe for easy use. Pipe Patch also has a perforated interior ring that can be removed to reinforce or repair 1 1/4" PVC drain pipe. Pipe Patch makes repairs strong, fast and easy. Same high-tech composite material as Strait-Flex.</p>
<p>ADVANTAGES</p>	<ul style="list-style-type: none"> • Fast, durable and low cost • Easy installation, material is pre-cut to fit copper pipe and has a perforated interior ring that can be removed to fit standard 1 1/4" PVC plumbing pipe • Will not sag • Material is not affected by water and damp conditions • Material can be second coated immediately • Requires very light fill coat to finish product • Will not fuzz-up during sanding like competitive fiber-glass-metal patches • Waterproof, rustproof • Average time for patch is 5-7 minutes
<p>WARRANTY</p>	<p>Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.</p>
<p>DIRECTIONS</p>	<ul style="list-style-type: none"> • Prepare surface by cleaning and lightly sand area around copper pipe. • Apply 1/4 of quick set or drywall compound directly to Pipe Patch. Flip over patch and position Pipe Patch around copper pipe and wipe down, removing excess compound between patch and drywall. Compound remains on back side of Pipe Patch in damaged or mis-cut areas makes Pipe Patch very rigid. • Apply second coat, let dry and sand. Pipe Patch will not fuzz up during sanding like competitive fiber glass-metal patches
<p>STORAGE</p>	<p>Store in dry place protected from moisture</p>

Submittal Approvals:

<p>Job Name:</p>	
<p>Contractor:</p>	<p>Date:</p>